

JANUS VALVES VALVE ORDERING CODE



PRESSURE RATING		MOUNTING		VALVE TYPE		PORT ORIFICE		ACTUATION	RETURN	FLUID	
*	(Bar)	*		*		*		*		*	
1	<30	Stand Alone	01	4/2	A	3	A	Solenoid 12VDC (No Card)	O	Other
2	Up to 160			02	4/3 Closed Centre	B	6	B	Solenoid 24VDC (Card Required)	S	Sea Water
3	>60* (*Relief Valve Only)	M	Janus Manifold	03	3/2 Spring to P Closed	C	9	C	Solenoid 48VDC (Card Required)	T	Tech. Water
4	25-100* (*Relief Valve Only)	C	CETOP-3	04	Priority Flow Control	D	12	D	Detent	W	Tap Water
				05	Relief (Inline)	E	16	E	----		
				06	4/3 Closed P	F	25	F	Air Pilot		
				07	Pressure Control (Janus)	G	38	G	Manual		
				08	3/2 Spring to P Open			H	Flow Controlled		
				09	Pressure Reducing			J	Water Pilot		
				10	Check			K	----		
				11	PO Check Single Port 3:1			L	Oil Pilot		
				12	4/3 Open Centre			M	----		
				13	PO Check Double Port 3:1			N	24VDC Proportional		
				14	4/3 P to A B at centre			O	24VDC (No Card)		
				15	Flow Divider			P	48VDC (No Card)		
				16	Pressure Compensated Flow Control			R	Stepper Motor Control		
				17	Solenoid Operated Un-Loader			S	Spring* (*Return Only)		
				18	----			X	Pressure		
				19	PO Check Single Port 9:1						
				20	----						
				21	2/2 Normally Open						
				22	PO Check Double Port 9:1						
				23	Electronic Flow Control						
				24	----						
				25	Electronic Pressure Control						
				26	2/2 Normally Closed						
				XX	Assembly						

Example:
 A Valve with a system operating pressure of 140 Bar, 4/3 Closed P, 6mm Ports, Manifold Mounted, 24V DC Solenoid actuated spring return for tap water.
(Note: Janus Control Valves stating (Card Req'd) require an actuation card as additional item. (Please refer to actuation card data sheet)

Ordering Code = **2 M 0 6 B B S W**